



Produktinformation		Product information	
<b>Produktbeskrivning:</b> Väggräcke med två rör monterat på C120 ständare monterade i mark		<b>Product description:</b> Safety barrier with two pipes fixed at C120 post installed in soil	
<b>Harmoniserad standard:</b> EN1317-5:2007/A2:2012		<b>Harmonised standard:</b> EN1317-5:2007 / A2:2012	
<b>Kapacitetsklass</b>	N2	<b>Containment level</b>	N2
<b>Ständaravstånd (m)</b>	4.0	<b>Post spacing (m)</b>	4.0
<b>Norm. arbetsbredd (klass)</b>	W3	<b>Norm. working width (class)</b>	W3
<b>Norm. arbetsbredd (m)</b>	0.9	<b>Norm. working width (m)</b>	0.9
<b>Norm. dynamisk utböjning (m)</b>	0.8	<b>Norm. dynamic deflection (m)</b>	0.8
<b>Skaderiskklass</b>	A	<b>Impact severity level</b>	A
<b>Konstruktionsbredd (m)</b>	0.21	<b>Construction width (m)</b>	0.21
<b>Konstruktionshöjd (m)</b>	0.73	<b>Construction height (m)</b>	0.73
<b>Motstånd mot snöplogning(klass)</b>	4	<b>Resistance to snow removal(class)</b>	4
<b>Beständighet:</b> Varmförzinkad enligt SS-EN ISO 1461:2009 Nationell Bilaga Fe/Zn 115		<b>Durability:</b> Hot dip galvanized coatings according to SS-EN ISO 1461:2009 National Annex. Fe/Zn 115	