



Produktinformation	Product information
<b>Produktbeskrivning:</b> Vägräcke med rör monterat på distanselement och C120 ståndare monterade i mark	<b>Product description:</b> Safety barrier with pipes fixed at distance element and C120 post installed in soil
<b>Harmoniserad standard:</b> EN1317-5:2007/A2:2012	<b>Harmonised standard:</b> EN1317-5:2007 / A2:2012
<b>Kapacitetsklass</b> H1	<b>Containment level</b> H1
<b>Ståndaravstånd (m)</b> 4	<b>Post spacing (m)</b> 4
<b>Norm. fordonsinträngning (klass)</b> VI6	<b>Norm. vehicle intrusion (class)</b> VI6
<b>Norm. fordonsinträngning (m)</b> 2.0	<b>Norm. vehicle intrusion (m)</b> 2.0
<b>Normaliserad arbetsbredd (klass)</b> W3	<b>Normalised working width (class)</b> W3
<b>Normaliserad arbetsbredd (m)</b> 1.0	<b>Normalised working width (m)</b> 1.0
<b>Normaliserad dynamisk utböj. (m)</b> 0.9	<b>Normalised dynamic defl. (m)</b> 0.9
<b>Skaderiskklass</b> A	<b>Impact severity level</b> A
<b>Konstruktionsbredd (m)</b> 0.33	<b>Construction width (m)</b> 0.33
<b>Konstruktionshöjd (m)</b> 0.73	<b>Construction height (m)</b> 0.73
<b>Motstånd mot snöplogning(klass)</b> 4	<b>Resistance to snow removal(class)</b> 4
<b>Beständighet:</b> Varmförzinkad enligt SS-EN ISO 1461:2009 Nationell Bilaga Fe/Zn 115	<b>Durability:</b> Hot dip galvanized coatings according to SS-EN ISO 1461:2009 National Annex. Fe/Zn 115