



Produktinformation		Product information	
Produktbeskrivning: Vägräcke med rör monterat på distanselement och C120 ståndare monterade i mark		Product description: Safety barrier with pipes fixed at distance element and C120 post installed in soil	
Harmoniserad standard: EN1317-5:2007/A2:2012		Harmonised standard: EN1317-5:2007 / A2:2012	
Kapacitetsklass	H2	Containment level	H2
Ständaravstånd (m)	2	Post spacing (m)	2
Norm. fordonsinträngning (klass)	VI5	Norm. vehicle intrusion (class)	VI5
Norm. fordonsinträngning (m)	1.5	Norm. vehicle intrusion (m)	1.5
Normaliserad arbetsbredd (klass)	W4	Normalised working width (class)	W4
Normaliserad arbetsbredd (m)	1.2	Normalised working width (m)	1.2
Normaliserad dynamisk utböj. (m)	1.1	Normalised dynamic defl. (m)	1.1
Skaderiskklass	A	Impact severity level	A
Konstruktionsbredd (m)	0.40	Construction width (m)	0.40
Konstruktionshöjd (m)	0.73	Construction height (m)	0.73
Motstånd mot snöplogning(klass)	4	Resistance to snow removal(class)	4
Beständighet: Varmförzinkad enligt SS-EN ISO 1461:2009 Nationell Bilaga Fe/Zn 115		Durability: Hot dip galvanized coatings according to SS-EN ISO 1461:2009 National Annex. Fe/Zn 115	