



Produktinformation		Product information	
Produktbeskrivning: Vägräcke med W-profil monterat på C120 ståndare monterade i mark		Product description: Safety barrier with A-profile fixed at C120 post installed in soil	
Harmoniserad standard: EN1317-5:2007/A2:2012		Harmonised standard: EN1317-5:2007 / A2:2012	
Kapacitetsklass	H1	Containment level	H1
Ståndaravstånd (m)	4.0	Post spacing (m)	4.0
Norm. fordonsinträngning (klass)	VI6	Norm. vehicle intrusion (class)	VI6
Norm. fordonsinträngning (m)	2.1	Norm. vehicle intrusion (m)	2.1
Normaliserad arbetsbredd (klass)	W3	Normalised working width (class)	W3
Normaliserad arbetsbredd (m)	1.0	Normalised working width (m)	1.0
Normaliserad dynamisk utböj. (m)	0.9	Normalised dynamic defl. (m)	0.9
Skaderiskklass	A	Impact severity level	A
Konstruktionsbredd (m)	0.20	Construction width (m)	0.20
Konstruktionshöjd (m)	0.73	Construction height (m)	0.73
Motstånd mot snöplogning(klass)	3	Resistance to snow removal(class)	3
Beständighet: Varmförzinkad enligt SS-EN ISO 1461:2009 Nationell Bilaga Fe/Zn 115		Durability: Hot dip galvanized coatings according to SS-EN ISO 1461:2009 National Annex. Fe/Zn 115	