



Produktinformation		Product information	
<b>Produktbeskrivning:</b> Väggräcke med W-profil monterat på $\phi 101.6$ ständare monterade i mark		<b>Product description:</b> Safety barrier with A-profile fixed at $\phi 101.6$ post installed in soil	
<b>Harmoniserad standard:</b> EN1317-5:2007/A2:2012		<b>Harmonised standard:</b> EN1317-5:2007 / A2:2012	
<b>Kapacitetsklass</b>	H2	<b>Containment level</b>	H2
<b>Ständaravstånd (m)</b>	1.33/2.0	<b>Post spacing (m)</b>	1.33/2.0
<b>Norm. fordonsinträngning (klass)</b>	VI6/VI4	<b>Norm. vehicle intrusion (class)</b>	VI6/VI4
<b>Norm. fordonsinträngning (m)</b>	1.9/1.3	<b>Norm. vehicle intrusion (m)</b>	1.9/1.3
<b>Normaliserad arbetsbredd (klass)</b>	W2/W4	<b>Normalised working width (class)</b>	W2/W4
<b>Normaliserad arbetsbredd (m)</b>	0.8/1.1	<b>Normalised working width (m)</b>	0.8/1.1
<b>Normaliserad dynamisk utböj. (m)</b>	0.8/1.0	<b>Normalised dynamic defl. (m)</b>	0.8/1.0
<b>Skaderiskklass</b>	B	<b>Impact severity level</b>	B
<b>Konstruktionsbredd (m)</b>	0.19	<b>Construction width (m)</b>	0.19
<b>Konstruktionshöjd (m)</b>	0.75	<b>Construction height (m)</b>	0.75
<b>Motstånd mot snöplogning(klass)</b>	3	<b>Resistance to snow removal(class)</b>	3
<b>Beständighet:</b> Varmförzinkad enligt SS-EN ISO 1461:2009		<b>Durability:</b> Hot dip galvanized coatings according to SS-EN ISO 1461:2009	