



| Produktinformation                                                                          |      | Product information                                                                                       |      |
|---------------------------------------------------------------------------------------------|------|-----------------------------------------------------------------------------------------------------------|------|
| <b>Produktbeskrivning:</b> Vägräcke med W-profil monterat på C120 ståndare monterade i mark |      | <b>Product description:</b> Safety barrier with A-profile fixed at C120 post installed in soil            |      |
| <b>Harmoniserad standard:</b> EN1317-5:2007/A2:2012                                         |      | <b>Harmonised standard:</b> EN1317-5:2007 / A2:2012                                                       |      |
| <b>Kapacitetsklass</b>                                                                      | N2   | <b>Containment level</b>                                                                                  | N2   |
| <b>Ståndaravstånd (m)</b>                                                                   | 1.33 | <b>Post spacing (m)</b>                                                                                   | 1.33 |
| <b>Normaliserad arbetsbredd (klass)</b>                                                     | W1   | <b>Normalised working width (class)</b>                                                                   | W1   |
| <b>Normaliserad arbetsbredd (m)</b>                                                         | 0.6  | <b>Normalised working width (m)</b>                                                                       | 0.6  |
| <b>Normaliserad dynamisk utböj. (m)</b>                                                     | 0.5  | <b>Normalised dynamic defl. (m)</b>                                                                       | 0.5  |
| <b>Skaderiskklass</b>                                                                       | B    | <b>Impact severity level</b>                                                                              | B    |
| <b>Konstruktionsbredd (m)</b>                                                               | 0.20 | <b>Construction width (m)</b>                                                                             | 0.20 |
| <b>Konstruktionshöjd (m)</b>                                                                | 0.73 | <b>Construction height (m)</b>                                                                            | 0.73 |
| <b>Motstånd mot snöplogning(klass)</b>                                                      | 3    | <b>Resistance to snow removal(class)</b>                                                                  | 3    |
| <b>Beständighet:</b> Varmförzinkad enligt SS-EN ISO 1461:2009 Nationell Bilaga Fe/Zn 115    |      | <b>Durability:</b> Hot dip galvanized coatings according to SS-EN ISO 1461:2009 National Annex. Fe/Zn 115 |      |