



Produktinformation		Product information	
<b>Produktbeskrivning:</b> Vagräcke med W-profil monterat på sigma ständare monterade i mark		<b>Product description:</b> Safety barrier with A-profile fixed at sigma post installed in soil	
<b>Harmoniserad standard:</b> EN1317-5:2007/A2:2012		<b>Harmonised standard:</b> EN1317-5:2007 / A2:2012	
<b>Kapacitetsklass</b>	N2	<b>Containment level</b>	N2
<b>Ständaravstånd (m)</b>	2 4	<b>Post spacing (m)</b>	2 4
<b>Normaliserad arbetsbredd (klass)</b>	W4 W5	<b>Normalised working width (class)</b>	W4 W5
<b>Normaliserad arbetsbredd (m)</b>	1.1 1.7	<b>Normalised working width (m)</b>	1.1 1.7
<b>Normaliserad dynamisk utböj. (m)</b>	0.9 1.5	<b>Normalised dynamic defl. (m)</b>	0.9 1.5
<b>Skaderiskklass</b>	A	<b>Impact severity level</b>	A
<b>Konstruktionsbredd (m)</b>	0.18	<b>Construction width (m)</b>	0.18
<b>Konstruktionshöjd (m)</b>	0.70	<b>Construction height (m)</b>	0.70
<b>Motstånd mot snöplogning(klass)</b>	3	<b>Resistance to snow removal(class)</b>	3
<b>Beständighet:</b> Varmförzinkad enligt SS-EN ISO 1461:2009 Nationell Bilaga Fe/Zn 115		<b>Durability:</b> Hot dip galvanized coatings according to SS-EN ISO 1461:2009 National Annex. Fe/Zn 115	