



Produktinformation		Product information	
Produktbeskrivning: Vagräcke med SF-profil monterat på $\phi 101.6$ ständare monterade i mark		Product description: Safety barrier with SF-profile fixed at $\phi 101.6$ post installed in soil	
Harmoniserad standard: EN1317-5:2007/A2:2012		Harmonised standard: EN1317-5:2007 / A2:2012	
Kapacitetsklass	H2	Containment level	H2
Ständaravstånd (m)	1.0/1.5	Post spacing (m)	1.0/1.5
Norm. fordonsinträngning (klass)	VI4/VI5	Norm. vehicle intrusion (class)	VI4/VI5
Norm. fordonsinträngning (m)	1.2/1.7	Norm. vehicle intrusion (m)	1.2/1.7
Normaliserad arbetsbredd (klass)	W3/W4	Normalised working width (class)	W3/W4
Normaliserad arbetsbredd (m)	1.0/1.2	Normalised working width (m)	1.0/1.2
Normaliserad dynamisk utböj. (m)	1.0/1.1	Normalised dynamic defl. (m)	1.0/1.1
Skaderiskklass	B	Impact severity level	B
Konstruktionsbredd (m)	0.16	Construction width (m)	0.16
Konstruktionshöjd (m)	0.72	Construction height (m)	0.72
Motstånd mot snöplogning(klass)	4	Resistance to snow removal(class)	4
Beständighet: Varmförzinkad enligt SS-EN ISO 1461:2009		Durability: Hot dip galvanized coatings according to SS-EN ISO 1461:2009	